

High Performance (HP) Tanking Primer

Page 1 of 3



- Suitable for green concrete and damp surfaces
- Suitable for application in low temperatures
- Highly penetrative formulation
- Significantly improves bond of torch applied and self adhesive membranes
- Quick and easy to apply
- Manufactured in the UK

Description

Visqueen High Performance Tanking Primer is a black, elastomeric bituminous priming solution designed to prepare surfaces prior to the application of Visqueen self adhesive and torch applied damp proofing and tanking membranes. The product is manufactured in the UK and supplied in 5L tins.

Uses

Visqueen High Performance Tanking Primer can be used to prepare a variety of substrates including metal, concrete, brickwork, blockwork and stonework. It significantly improves the bond of Visqueen self adhesive and torch applied damp proofing and tanking membranes and helps to ensure a long-term watertight finish. It is suitable for green concrete, damp surfaces or substrate temperatures below 5C.

Application

Visqueen High Performance Tanking Primer can be applied by brush or roller. Care should be taken to prevent splashes as primer will permanently stain porous surfaces.

Surfaces must be smooth, clean, and free from contaminants such as dust, dirt, grease, lichen, frost, etc. Substrate temperature must be greater than -4C.

Coverage rates on porous surfaces e.g. concrete is 6–8m²/litre.

Visqueen High Performance Tanking Primer will dry in 2–8 hours depending upon temperature, surface porosity and ventilation. Wait until primer is tack free. The primer will be resistant to light rainfall almost immediately after application. Allow to dry fully before application of waterproofing membrane.

Avoid pouring the primer directly onto a horizontal surface; use a dip tray. The primer should not be allowed to puddle during application as this will increase drying time.

All tools can be cleaned after use with white spirit.

VISQUEEN
BUILDING PRODUCTS

Heanor Gate, Heanor, Derbyshire DE75 7RG

T: 0845 302 4758 F: 0845 017 8663

enquiries@visqueenbuilding.co.uk

www.visqueenbuilding.co.uk

VISQUEEN BUILDING PRODUCTS IS A TRADING NAME
 OF BRITISH POLYTHENE LIMITED, COMPANY NUMBER:
 350729, REGISTERED OFFICE: ONE LONDON WALL,
 LONDON, EC2Y 5AB

STRUCTURAL WATERPROOFING
 AND GAS PROTECTION SYSTEMS

High Performance (HP) Tanking Primer

Priming should be limited to an area that can be covered with membrane in 24 hours. Areas that accumulate significant amounts of dust or dirt must be re-primed before membrane application.

When used on green concrete or damp surfaces, moisture may become trapped under the membrane which may result in blistering, particularly in warm, sunny weather. To reduce this risk, the membrane should be covered as soon as possible after application.

SPECIFICATION SUPPORT

The following items are available to view online or to download from www.visqueenbuilding.co.uk

- . Technical Datasheets
- . Typical installation CAD details
- . Health and Safety data

Register online for access to NBS Clauses and for information about our CPD Seminars



TECHNICAL SUPPORT

For advice on detailing or installation call Visqueen Building Products Technical Help Line 0845 302 4758. Pricing & Availability may be obtained from our UK Network of merchant stockists. For details of these call our Sales Office on 0845 302 4758.

VISQUEEN
BUILDING PRODUCTS

High Performance (HP) Tanking Primer

Page 3 of 3

Storage

Containers should be kept sealed in a cool, dry, well-ventilated environment out of direct sunlight.

Partly used containers may be resealed and used again after correct storage. To avoid the risk of spillage, always store and transport in a secure upright position.

Health and Safety

Visqueen High Performance Tanking Primer contains a flammable solvent. In use, prevent a build up of solvent vapour by providing adequate ventilation. Exposure to vapour can cause dizziness and should this occur remove affected person to fresh air and seek medical attention if required. Avoid contact with skin and eyes. Should there be contact with skin, wash immediately with soap and water or a recognised skin cleaner. In case of contact with eyes, rinse immediately with plenty of water and seek medical attention.

Do not use in the presence of sources of ignition. Do not smoke when using the primer. In the event of fire, extinguish using CO₂, dry powder or foam extinguishers, sand or earth.

Technical Support

Visqueen Building Products offer a responsive technical service and can provide advice on any damp proofing, ground gas protection or tanking application including product selection and suitability, installation advice, design assistance and product availability.

The information given in this datasheet is based on data and knowledge correct at the time of printing. Statements made are of a general nature and are not intended to apply to any use or application outside any referred to in the datasheet. As conditions of usage and installation are beyond our control we do not warrant performance obtained but strongly recommend that our installation guidelines and the relevant British Standard Codes of Practice are adhered to. Please contact us if you are in any doubt as to the suitability of application.

SPECIFICATION SUPPORT

The following items are available to view online or to download from www.visqueenbuilding.co.uk

- . Technical Datasheets
- . Typical installation CAD details
- . Health and Safety data

Register online for access to NBS Clauses and for information about our CPD Seminars



TECHNICAL SUPPORT

For advice on detailing or installation call Visqueen Building Products Technical Help Line 0845 302 4758. Pricing & Availability may be obtained from our UK Network of merchant stockists. For details of these call our Sales Office on 0845 302 4758.

VISQUEEN
BUILDING PRODUCTS