

Visqueen Liquid Gas Membrane Primer

Page 1 of 2



Description

Visqueen Liquid Gas Membrane Primer is part of Visqueen's liquid membrane system and used to prepare surfaces before the application of the main liquid membrane.

Visqueen Liquid Gas Membrane Primer is supplied in 5L drums and only requires agitation prior to use. Visqueen Liquid Gas Membrane Primer can be applied by brush, roller or airless spray.

Installation

For optimum performance, all substrates should be primed with Visqueen Liquid Gas Membrane Primer at a rate of 0.25 litre/m². Ensure that the primer is applied evenly and if spraying, use a circular action. Allow the primer to dry (approximately 2 hours depending upon surface, temperature, humidity and ventilation).

For recommended dilution rates please consult with our Visqueen technical team (0845 302 4758) as these can vary depending on the application.

Shelf life and Storage

Visqueen Liquid Gas Membrane Primer has a minimum shelf life of 12 months when stored in sealed containers at temperatures of 5°C to 25°C. The product must not be subjected to temperatures below 5°C during storage or transportation.

Temperatures below 5°C will render the product unfit for use. Store in a dry location out of direct sunlight.

Health and Safety

Visqueen Liquid Gas Membrane Primer's Health and Safety datasheet is available on our website or on request and should be read prior to product use.

VISQUEEN
BUILDING PRODUCTS

Heanor Gate, Heanor, Derbyshire DE75 7RG

T: 0845 302 4758 F: 0845 017 8663

enquiries@visqueenbuilding.co.uk

www.visqueenbuilding.co.uk

VISQUEEN BUILDING PRODUCTS IS A TRADING NAME
OF BRITISH POLYTHENE LIMITED, COMPANY NUMBER:
350729, REGISTERED OFFICE: ONE LONDON WALL,
LONDON, EC2Y 5AB

STRUCTURAL WATERPROOFING
AND GAS PROTECTION SYSTEMS

Visqueen Liquid Gas Membrane Primer

Page 2 of 2

The information given in this datasheet is based on data and knowledge correct at the time of printing. Statements made are of a general nature and are not intended to apply to any use or application outside any referred to in the datasheet. As conditions of usage and installation are beyond our control we do not warrant performance obtained but strongly recommend that our installation guidelines and the relevant British Standard Codes of Practice are adhered to. Please contact us if you are in any doubt as to the suitability of application.

SPECIFICATION SUPPORT

The following items are available to view online or to download from

www.visqueenbuilding.co.uk

- . Technical Datasheets
- . Typical installation CAD details
- . Health and Safety data

Register online for access to NBS Clauses and for information about our CPD Seminars



TECHNICAL SUPPORT

For advice on detailing or installation call Visqueen Building Products Technical Help Line 0845 302 4758. Pricing & Availability may be obtained from our UK Network of merchant stockists. For details of these call our Sales Office on 0845 302 4758.

VISQUEEN
BUILDING PRODUCTS